

GEKO 9001 E-S/SEBA

Order number : **V5048**

El. capacity 1 ~ : **9,2 kVA = 7,36kW** Steady state
Power factor : $\cos \varphi = 0,8$
Voltage 1~ : 230V
Max. sum. current 1 ~ : 40 A
Current1~(CEE) : 40 A
Current1~(Schuko) : 16 A
Max. starting current
Cos φ 0,6 1 ~ : 60 A
Frequency : 50 Hz
Noise pressure (10m Distance) : **70 dB(A)**
Length x Width x Height : 790mm x 550mm x 650mm
Weight : 138 kg

Engine

Producer : Briggs & Stratton
Type : 380447 (Petrol)
Operating mode : 4-Stroke, 3000 ^{1/min} / 1800 ^{1/min}
Number of cylinders : 2
Fuel consumption by
25% / 50% / 75% / 100% load : 2,54l/h / 3,36l/h / 4,46l/h / 5,52l/h
Cooling system : Air
Engine power : 12,1 kW
Start system : Electro start

Generator

Type : Synchronous
Cooling System : Air
Safety class : IP 54

Filling quantity

Engine oil : 1,7 Litre
Fuel tank : 10 Litre

Control panel and connections

- 1 x Recoil hand starter
- 2 x Plug socket 1~ 230V/16A (Schuko)
- 1 x Plug socket 1~ 230V/63A (CEE)
- 1 x Operating time counter

